



ARAT E

Discretion meets elegance. Practicality meets style. 40 different sizes for total versatility, with a heat kick that belies its subtle appearance. Ideal for when wall space is at a premium.

R Model shown on opposite page: ARE8-5050-S (brushed matt)

ARAT E

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V H MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
ARE855	500	390	40	E/H/D	8	1441	422	300	340	S, P
ARE1055	500	490	40	E/H/D	10	1790	524	300	340	S, P
ARE1255	500	590	40	E/H/D	12	2138	626	300	340	S, P
ARE1455	500	690	40	E/H/D	14	2493	730	300	340	S, P
ARE1655	500	790	40	E/H/D	16	2835	830	300	340	S, P
ARE2055	500	990	40	E/H/D	20	3532	1034	300	340	S, P
ARE2455	500	1190	40	H	24	4229	1238	H: Central Heating Only		S, P
ARE2855	500	1390	40	H	28	4925	1442	H: Central Heating Only		S, P
ARE3255	500	1590	40	H	32	5622	1646	H: Central Heating Only		S, P
ARE3655	500	1790	40	H	36	6319	1850	H: Central Heating Only		S, P
ARE4055	500	1990	40	H	40	7016	2054	H: Central Heating Only		S, P
ARE866	600	390	40	E/H/D	8	1730	506	300	300	S, P
ARE1066	600	490	40	E/H/D	10	2148	629	300	300	S, P
ARE1266	600	590	40	E/H/D	12	2566	751	300	300	S, P
ARE1466	600	690	40	E/H/D	14	2992	876	300	300	S, P
ARE1666	600	790	40	E/H/D	16	3402	996	300	300	S, P
ARE2066	600	990	40	E/H/D	20	4238	1241	2x300		S, P
ARE2466	600	1190	40	H	24	5074	1486	H: Central Heating Only		S, P
ARE2866	600	1390	40	H	28	5910	1730	H: Central Heating Only		S, P
ARE3266	600	1590	40	H	32	6746	1975	H: Central Heating Only		S, P
ARE3666	600	1790	40	H	36	7583	2220	H: Central Heating Only		S, P
ARE4066	600	1990	40	H	40	8419	2465	H: Central Heating Only		S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)