









ARMADA

Striking, majestic and bold. This radiator will put you and your home firmly on the map. The versatile design allows great flexibility in the choice of length and number of columns.

R Model shown on opposite page: ARM1821-S (brushed matt) Above left: ARM1821-P (polished) Above right: ARM1821-G (brushed matt with gold laminated discs)

ARMADA													
		 SS		 10		 120°C		 O C		 V H		 20 YEARS	
		MATERIAL		WORKING PRESSURE		WORKING TEMP.		OPEN/CLOSED SYSTEM		MOUNT POSITION		WARRANTY	
Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished G: Gold Laminated / Brushed Matt			
								Choice of Elements (Watts)					
ARM1221	1200	210	95	E/H/D	4	1804	528	300	400	S, P, G			
ARM1521	1500	210	95	E/H/D	4	2295	672	300	400	S, P, G			
ARM1821	1800	210	95	E/H/D	4	2785	816	400	600	S, P, G			
ARM1247	1200	470	95	E/H/D	8	3609	1057	2 x 300		S, P, G			
ARM1547	1500	470	95	E/H/D	8	4590	1344	2 x 400		S, P, G			
ARM1847	1800	470	95	E/H/D	8	5571	1631	2 x 600		S, P, G			

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of “T” piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

