



ELIXIR

When is a table also a radiator? When it's a dramatic triangular heat source. Accompanied by a co-ordinating mirror, this will be the undisputed focal point of any room.

R Model shown on opposite page: ELX120-S (brushed matt) and ELXM120 (brushed matt frame) Mirror

ELIXIR

SS
MATERIAL

10
WORKING PRESSURE

120°C
WORKING TEMP.

O C
OPEN/CLOSED SYSTEM

V
MOUNT POSITION

20 YEARS
WARRANTY

| Product Name | Height (mm) | Length (mm) | Depth (mm) | Fuel Options (E/H/D) | Pipes or Sections | Heat Output (BTU/w) ΔT 50 | | E: Electric only | | Finish S: Brushed Matt P: Polished |
|------------------------|-------------|-------------|------------|----------------------|-------------------|-----------------------------------|------|----------------------------|-------|--|
| | | | | | | | | Choice of Elements (Watts) | | |
| ELX120 | 900 | 1200 | 255 | H | 30 | 11190 | 3277 | 2x600 | 2x900 | S |
| ELX150 | 900 | 1500 | 255 | H | 30 | 12425 | 3638 | 2x600 | 2x900 | S |
| ELXM120 (Mirror) | 630 | 840 | 60 | - | - | - | - | | | S |
| ELXM150 (Mirror) | 630 | 1050 | 60 | - | - | - | - | | | S |
| ELXGS120 (Glass Shelf) | 100 | 840 | 60 | - | - | - | - | | | S |
| ELXGS150 (Glass Shelf) | 100 | 1050 | 60 | - | - | - | - | | | S |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)

