



MARION

Subtle luxury. The simple design belies an easy elegance and versatile performance. This classic radiator will enhance any room of the house – no need to banish it to the kitchen or bathroom.

R Model shown on opposite page: MAL51816-S (brushed matt) Above left: MAL2076-S (brushed matt)

MARION L

SS MATERIAL
 8 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
MAL876	760	430	90	E/H/D	16	2739	802	300		S, P
MAL1076	760	530	90	E/H/D	20	3388	992	400		S, P
MAL1276	760	630	90	E/H/D	24	4037	1182	400		S, P
MAL1476	760	730	90	E/H/D	28	4686	1372	400		S, P
MAL1676	760	830	90	E/H/D	32	5335	1562	600		S, P
MAL2076	760	1030	90	E/H/D	40	6633	1942	600		S, P
MAL2476	760	1230	90	H	48	7931	2322	600	900	S, P
MAL2876	760	1430	90	H	56	9229	2702	900		S, P
MAL3276	760	1630	90	H	64	10527	3082	2x900	900	S, P
MAL3676	760	1830	90	H	72	11825	3462	2x600	2x900	S, P
MAL4076	760	2030	90	H	80	13123	3842	2x600	2x900	S, P
MAL71513	1500	380	80	H	14	5082	1488	340	400	S, P
MAL51816	1800	280	80	H	10	4471	1309	H: Central Heating Only		S, P
MAL61816	1800	330	80	H	12	5335	1562	340	400	S, P
MAL52018	2000	280	80	H	10	5011	1467	H: Central Heating Only		S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)