

MYSTIC

This is no illusion. The cleverly designed tubular columns appear to hang in the air, while the heat generated is nothing short of miraculous. Ethereal elegance meets stylish stainless steel.

 Model shown on opposite page: MYE608-S (brushed matt)

MYSTIC E

 MATERIAL
  WORKING PRESSURE
  WORKING TEMP.
  OPEN/CLOSED SYSTEM
  MOUNT POSITION
  WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
MYE405	400	340	90	E/H/D	10	1127	330	340	400	S, P
MYE406	400	410	90	E/H/D	12	1353	396	340	400	S, P
MYE407	400	480	90	E/H/D	14	1578	462	340	400	S, P
MYE408	400	550	90	E/H/D	16	1803	528	340	400	S, P
MYE409	400	620	90	E/H/D	18	2029	594	340	400	S, P
MYE410	400	690	90	E/H/D	20	2254	660	400	600	S, P
MYE412	400	830	90	E/H/D	24	2705	792	400	600	S, P
MYE414	400	970	90	E/H/D	28	3156	924	400	600	S, P
MYE416	400	1110	90	E/H/D	32	3607	1056	400	600	S, P
MYE605	600	340	90	E/H/D	10	1691	495	600	900	S, P
MYE606	600	410	90	E/H/D	12	2029	594	340	400	S, P
MYE607	600	480	90	E/H/D	14	2367	693	340	400	S, P
MYE608	600	550	90	E/H/D	16	2705	792	400		S, P
MYE609	600	620	90	E/H/D	18	3043	891	400		S, P
MYE610	600	690	90	E/H/D	20	3381	990	600		S, P
MYE612	600	830	90	E/H/D	24	4058	1188	600		S, P
MYE614	600	970	90	E/H/D	28	4734	1386	600		S, P
MYE616	600	1110	90	E/H/D	32	5410	1584	600	900	S, P
MYE154	1500	270	90	E/H/D	8	3429	1004	340	400	S, P
MYE155	1500	340	90	E/H/D	10	4287	1255	340	400	S, P
MYE156	1500	410	90	E/H/D	12	5144	1506	340	400	S, P
MYE158	1500	550	90	E/H/D	16	6859	2008	340	400	S, P
MYE184	1800	270	90	E/H/D	8	4085	1196	340	400	S, P
MYE185	1800	340	90	E/H/D	10	5106	1495	340	400	S, P
MYE204	2000	270	90	E/H/D	8	4550	1332	340	400	S, P
MYE205	2000	340	90	E/H/D	10	5687	1665	340	400	S, P
MYE206	2000	410	90	E/H/D	12	6824	1998	340	400	S, P
MYE207	2000	480	90	E/H/D	14	7962	2331	340	400	S, P
MYE208	2000	550	90	E/H/D	16	9099	2664	340	400	S, P

MYSTIC L

MOUNT POSITION 

MYL808	780	550	90	E/H/D	16	2842	832	340	400	S, P
MYL809	780	620	90	E/H/D	18	3197	936	340	400	S, P
MYL810	780	690	90	E/H/D	20	3552	1040	400	600	S, P
MYL812	780	830	90	E/H/D	24	4263	1248	600		S, P
MYL814	780	970	90	E/H/D	28	4973	1456	600		S, P
MYL816	780	1110	90	E/H/D	32	5684	1664	600	900	S, P
MYL820	780	1390	90	E/H/D	40	7104	2080	600	900	S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)