



Model shown with chrome trim



Model shown with gold trim

SEREN

Cool stainless steel provides a practical, elegant place to keep towels warm. Spacious enough to accommodate even the largest family at bath-time and superbly crafted to ensure a flawless finish.

T Model shown on opposite page: SE175-55-S (brushed matt)

SEREN

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V MOUNT POSITION
 20 YEARS WARRANTY

| Product Name | Height (mm) | Length (mm) | Depth (mm) | Fuel Options (E/H/D) | Towel Gaps | Pipes or Sections | Heat Output (BTU/w) ΔT 50 | | E: Electric only | | Finish S: Brushed Matt P: Polished |
|--------------|-------------|-------------|------------|----------------------|------------|-------------------|---------------------------|------|----------------------------|-----|--|
| | | | | | | | | | Choice of Elements (Watts) | | |
| SE75 | 750 | 550 | 32 | E/H/D | 1 | 14 | 1599 | 468 | 300 | 400 | S, P |
| SE76 | 750 | 650 | 32 | E/H/D | 1 | 14 | 1817 | 532 | 300 | 400 | S, P |
| SE105 | 1000 | 550 | 32 | E/H/D | 2 | 18 | 2271 | 665 | 400 | 600 | S, P |
| SE135 | 1300 | 550 | 32 | E/H/D | 2 | 22 | 2439 | 714 | 400 | 600 | S, P |
| SE136 | 1300 | 650 | 32 | E/H/D | 2 | 22 | 2862 | 838 | 400 | 600 | S, P |
| SE175 | 1750 | 550 | 32 | E/H/D | 3 | 30 | 3651 | 1069 | 600 | 900 | S, P |
| SE176 | 1750 | 650 | 32 | E/H/D | 3 | 30 | 4266 | 1249 | 600 | 900 | S, P |
| SE75C | 750 | 550 | 32 | E/H/D | 1 | 14 | 1599 | 468 | 300 | 400 | S |
| SE76C | 750 | 650 | 32 | E/H/D | 1 | 14 | 1817 | 532 | 300 | 400 | S |
| SE105C | 1000 | 550 | 32 | E/H/D | 2 | 18 | 2271 | 665 | 400 | 600 | S |
| SE135C | 1300 | 550 | 32 | E/H/D | 2 | 22 | 2439 | 714 | 400 | 600 | S |
| SE136C | 1300 | 650 | 32 | E/H/D | 2 | 22 | 2862 | 838 | 400 | 600 | S |
| SE175C | 1750 | 550 | 32 | E/H/D | 3 | 30 | 3651 | 1069 | 600 | 900 | S |
| SE176C | 1750 | 650 | 32 | E/H/D | 3 | 30 | 4266 | 1249 | 600 | 900 | S |
| SE75G | 750 | 550 | 32 | E/H/D | 1 | 14 | 1599 | 468 | 300 | 400 | S |
| SE76G | 750 | 650 | 32 | E/H/D | 1 | 14 | 1817 | 532 | 300 | 400 | S |
| SE105G | 1000 | 550 | 32 | E/H/D | 2 | 18 | 2271 | 665 | 400 | 600 | S |
| SE135G | 1300 | 550 | 32 | E/H/D | 2 | 22 | 2439 | 714 | 400 | 600 | S |
| SE136G | 1300 | 650 | 32 | E/H/D | 2 | 22 | 2862 | 838 | 400 | 600 | S |
| SE175G | 1750 | 550 | 32 | E/H/D | 3 | 30 | 3651 | 1069 | 600 | 900 | S |
| SE176G | 1750 | 650 | 32 | E/H/D | 3 | 30 | 4266 | 1249 | 600 | 900 | S |

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)