



SUPRA

The perfect finishing touch to an ultra-modern bathroom. This slim, dynamic design will enhance everyone's favourite room and set the mood for a luxurious pampering session.

R Model shown on opposite page: SUPD

SUPRA DOUBLE

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V H MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
SUPD48	450	880	50	E/H/D	34	3863	1131	600		S, P
SUPD64	600	440	50	E/H/D	18	2606	763	340	400	S, P
SUPD65	600	550	50	E/H/D	22	3241	949	400		S, P
SUPD66	600	660	50	E/H/D	26	3877	1135	400		S, P
SUPD67	600	770	50	E/H/D	30	4512	1321	600		S, P
SUPD84	800	440	50	E/H/D	18	3518	1030	340	400	S, P
SUPD85	800	550	50	E/H/D	22	4375	1281	400		S, P
SUPD86	800	660	50	E/H/D	26	5233	1532	400		S, P
SUPD103	1000	330	50	E/H/D	14	3286	962	340	400	S, P
SUPD104	1000	440	50	H	18	4348	1273	H: Central Heating Only		S, P
SUPD105	1000	550	50	E/H/D	22	5407	1583	400		S, P
SUPD106	1000	660	50	E/H/D	26	6466	1893	400		S, P
SUPD122	1200	220	50	H	10	2671	782	H: Central Heating Only		S, P
SUPD123	1200	330	50	H	14	3945	1155	H: Central Heating Only		S, P
SUPD124	1200	440	50	H	18	5216	1527	H: Central Heating Only		S, P
SUPD125	1200	550	50	H	22	6490	1900	H: Central Heating Only		S, P
SUPD126	1200	660	50	E/H/D	26	7760	2272	400		S, P
SUPD152	1500	220	50	H	10	3340	978	H: Central Heating Only		S, P
SUPD153	1500	330	50	H	14	4929	1443	340	400	S, P
SUPD154	1500	440	50	H	18	6520	1909	H: Central Heating Only		S, P
SUPD155	1500	550	50	E/H/D	22	8112	2375	400		S, P
SUPD182	1800	220	50	H	10	4006	1173	H: Central Heating Only		S, P
SUPD183	1800	330	50	H	14	5912	1731	H: Central Heating Only		S, P
SUPD184	1800	440	50	H	18	7818	2289	H: Central Heating Only		S, P
SUPD185	1800	550	50	E/H/D	22	9728	2848	400		S, P
SUPD202	2000	220	50	H	10	4454	1304	H: Central Heating Only		S, P
SUPD203	2000	330	50	H	14	6572	1924	H: Central Heating Only		S, P
SUPD204	2000	440	50	H	18	8682	2542	H: Central Heating Only		S, P
SUPD205	2000	550	50	E/H/D	22	10814	3166	400		S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)