



SUPRA

SUPRA TRIPLE

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V H MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only	Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)	
SUPT45	450	550	70	H	31	3247	951	H: Central Heating Only	S, P
SUPT46	450	660	70	H	37	3885	1137	H: Central Heating Only	S, P
SUPT47	450	770	70	E/H/D	43	4520	1323	600	S, P
SUPT48	450	880	70	E/H/D	49	5159	1510	600	S, P
SUPT64	600	440	70	H	25	3481	1019	H: Central Heating Only	S, P
SUPT65	600	550	70	H	31	4329	1267	H: Central Heating Only	S, P
SUPT66	600	660	70	H	37	5177	1516	H: Central Heating Only	S, P
SUPT67	600	770	70	E/H/D	43	6025	1764	600	S, P
SUPT84	800	440	70	H	25	4697	1375	H: Central Heating Only	S, P
SUPT85	800	550	70	H	31	5843	1711	H: Central Heating Only	S, P
SUPT86	800	660	70	H	37	6986	2045	H: Central Heating Only	S, P
SUPT103	1000	330	70	H	19	4387	1284	H: Central Heating Only	S, P
SUPT104	1000	440	70	H	25	5806	1700	H: Central Heating Only	S, P
SUPT105	1000	550	70	H	31	7220	2114	H: Central Heating Only	S, P
SUPT106	1000	660	70	H	37	8633	2528	H: Central Heating Only	S, P
SUPT122	1200	220	70	H	13	3566	1044	H: Central Heating Only	S, P
SUPT123	1200	330	70	H	19	5268	1542	H: Central Heating Only	S, P
SUPT124	1200	440	70	H	25	6964	2039	H: Central Heating Only	S, P
SUPT125	1200	550	70	H	31	8664	2537	H: Central Heating Only	S, P
SUPT126	1200	660	70	H	37	10360	3033	H: Central Heating Only	S, P
SUPT152	1500	220	70	H	13	4460	1306	H: Central Heating Only	S, P
SUPT153	1500	330	70	H	19	6581	1927	H: Central Heating Only	S, P
SUPT154	1500	440	70	H	25	8706	2549	H: Central Heating Only	S, P
SUPT155	1500	550	70	H	31	10831	3171	H: Central Heating Only	S, P
SUPT182	1800	220	70	H	13	5350	1566	H: Central Heating Only	S, P
SUPT183	1800	330	70	H	19	7895	2311	H: Central Heating Only	S, P
SUPT184	1800	440	70	V	25	10439	3056	H: Central Heating Only	S, P
SUPT185	1800	550	70	V	31	12986	3802	H: Central Heating Only	S, P
SUPT202	2000	220	70	H	13	5946	1741	H: Central Heating Only	S, P
SUPT203	2000	330	70	V	19	8773	2569	H: Central Heating Only	S, P
SUPT204	2000	440	70	V	25	11591	3394	H: Central Heating Only	S, P
SUPT205	2000	550	70	V	31	14436	4227	H: Central Heating Only	S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)