

## TUBO

Quirky isn't the word. The fun combination of wide tubular rows connected to two slim columns is sure to please, and is versatile enough to suit any style of bathroom.

Model shown on opposite page: TUB508-S (brushed matt) Above Left: TUB506-P (polished)

TUBO					SS	10	120°C		0 0	V	20 YEARS	
				MAT	TERIAL V	VORKING PRESSURE	WORKING TE	EMP. OPEN	CLOSED SYSTEM	MOUNT POSITION	ON WARRANTY	
Product	Height	Length	Depth	Fuel	Towel	Pipes	Heat Output (BTU/w) ΔT 50		E: Electri	c only	Finish	
Name	(mm)	(mm)	(mm)	Options (E/H/D)	Gaps	or Sections			Choice of E (Wat		S: Brushed Matt P: Polished	
TUB506	705	500	60	E/H/D	2	12	1496	438	300	)	S, P	
TUB508	990	500	60	E/H/D	3	16	1994	584	400	)	S, P	
TUB510	1275	500	60	E/H/D	4	20	2493	730	400		S, P	
TUB512	1560	500	60	E/H/D	5	24	2992	876	2x34	-0	S, P	

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)





