

Kcal = Watt x 0.860  
BTU = Watt x 3.413

Watt Δt 60° = Watt Δt 50° x 1.241  
Watt Δt 40° = Watt Δt 50° x 0.768  
Watt Δt 30° = Watt Δt 50° x 0.546  
Watt Δt 20° = Watt Δt 50° x 0.338

p max = 10.0 bar

**Oreste**

H cm	L cm	I* cm	art*	Lt*	watt Δt 30°	watt Δt 50°
172.0	34.0	5.0	<b>OEO172001_</b>	1.7	202	<b>370</b>

**Emma**

H cm	L cm	I* cm	art*	Lt*	watt Δt 30°	watt Δt 50°
172.0	34.0	5.0	<b>OEE172001_</b>	1.7	202	<b>370</b>

watt Δt 30°	watt Δt 50°
141	<b>259</b>

watt Δt 30°	watt Δt 50°
141	<b>259</b>

**CRSM** Brushed chrome / Chrome brossé / Gebürstet Chrome / Cromo cepillado

**GLSM** Brushed gold / Dorè brossé / Gebürstet Gold / Oro cepillado

**Optional**




Angled monotube Valve  
Vanne monotube équerre  
Eijjrohrige Ventil  
Válvula monotubo a escuadra

[BIAN] **E12MBSQB**  
[CROM] **E12MBSQR**



Thermostatic head  
Tête thermostatique  
Thermostatkopf  
Cabezal termostático

[BIAN] **TTB**  
[CROM] **TTR**



Sleeving kit  
Kit couvre tuyau  
Rosetten  
Kit cubre tubo

[BIAN] **C5B**  
[CROM] **C5R**

art\* = item / modèle / Artikel / artículo I\* = pipe centres / distance entre depart et retour / Achsabstand / distancia entre las conexiones

Lt\* = water content for each element / volume d'eau pour chaque element / Wassergehalt für Element / contenido de agua por cada elemento

P\* = page / page / Seite / página