



Image for illustration purposes

Bombe

ALUMINIUM RADIATORS

Star quality. The convex and concave curves of this striking design allow light to bounce from its surfaces, creating a vision in heated aluminium perfection.



AL MATERIAL
 BAL 9010 MAH FINISH
 10 WORKING PRESSURE
 95 °C WORKING TEMP.
 C CLOSED SYSTEM
 V MOUNTING POS.
 10 YEARS WARRANTY

| PRODUCT NAME | DIMENSIONS | | | PIPE CENTRES mm | WALL TO PIPE CENTRE mm | WALL TO FACE mm | WATER CONTENT lt | GROSS WEIGHT kg | FUEL OPTIONS E/H/D | PIPES OR SECTIONS | HEAT OUTPUT AT AT 50 | |
|--------------|------------|-----------|----------|--------------------|---------------------------|--------------------|---------------------|--------------------|-----------------------|-------------------|----------------------|-------|
| | Height mm | Length mm | Depth mm | | | | | | | | BTU | Watts |
| BLU607 | 600 | 485 | 63 | 575-50 | 60 | 95 | 0.9 | 8.4 | H | 7 | 2104 | 616 |
| BLU609 | 600 | 625 | 63 | 715-50 | 60 | 95 | 1.2 | 10.8 | H | 9 | 2705 | 792 |
| BLU611 | 600 | 765 | 63 | 855-50 | 60 | 95 | 1.5 | 13.2 | H | 11 | 3306 | 968 |
| BLU613 | 600 | 905 | 63 | 995-50 | 60 | 95 | 1.7 | 15.6 | H | 13 | 3907 | 1144 |
| BLU614 | 600 | 975 | 63 | 1065-50 | 60 | 95 | 1.9 | 16.8 | H | 14 | 4207 | 1232 |
| BLU615 | 600 | 1045 | 63 | 1135-50 | 60 | 95 | 2.0 | 18.0 | H | 15 | 4508 | 1320 |
| BLU618 | 600 | 1255 | 63 | 1345-50 | 60 | 95 | 2.4 | 21.6 | H | 18 | 5409 | 1584 |
| BLU621 | 600 | 1465 | 63 | 1555-50 | 60 | 95 | 2.8 | 25.2 | H | 21 | 6311 | 1848 |
| BLU625 | 600 | 1745 | 63 | 1835-50 | 60 | 95 | 3.4 | 30.0 | H | 25 | 7513 | 2200 |
| BLU628 | 600 | 1955 | 63 | 2045-50 | 60 | 95 | 3.8 | 33.6 | H | 28 | 8415 | 2464 |
| BLU1505 | 1500 | 345 | 63 | 435-50 | 60 | 95 | 1.7 | 15.0 | H | 5 | 3087 | 904 |
| BLU1507 | 1500 | 485 | 63 | 575-50 | 60 | 95 | 2.3 | 21.0 | H | 7 | 4320 | 1265 |
| BLU1509 | 1500 | 625 | 63 | 715-50 | 60 | 95 | 3.0 | 27.0 | H | 9 | 5553 | 1626 |
| BLU1510 | 1500 | 695 | 63 | 785-50 | 60 | 95 | 3.3 | 30.0 | H | 10 | 6171 | 1807 |
| BLU1803 | 1800 | 205 | 63 | 295-50 | 60 | 95 | 1.2 | 10.8 | H | 3 | 2418 | 708 |
| BLU1804 | 1800 | 275 | 63 | 365-50 | 60 | 95 | 1.6 | 14.4 | H | 4 | 3224 | 944 |
| BLU1805 | 1800 | 345 | 63 | 435-50 | 60 | 95 | 2.0 | 18.0 | H | 5 | 4030 | 1180 |
| BLU1806 | 1800 | 415 | 63 | 505-50 | 60 | 95 | 2.4 | 21.6 | H | 6 | 4836 | 1416 |
| BLU1807 | 1800 | 485 | 63 | 575-50 | 60 | 95 | 2.8 | 25.2 | H | 7 | 5642 | 1652 |
| BLU1809 | 1800 | 625 | 63 | 715-50 | 60 | 95 | 3.6 | 32.4 | H | 9 | 7253 | 2124 |
| BLU2005 | 2000 | 345 | 63 | 435-50 | 60 | 95 | 2.2 | 20.1 | H | 5 | 4559 | 1335 |
| BLU2007 | 2000 | 485 | 63 | 575-50 | 60 | 95 | 3.1 | 28.0 | H | 7 | 6383 | 1869 |
| BLU2009 | 2000 | 625 | 63 | 715-50 | 60 | 95 | 4.0 | 36.0 | H | 9 | 8206 | 2403 |

Additional finish options are available:
Contact us for more information.

See Page 84 For Colours & Finishes

RECOMMENDED ACCESSORIES
See Page 87 For More Valves & Accessories



Corner Thermostatic Valve & TRV Head
UAW853CT



Cylindrical-25 Straight Manual Rad. Valve + L/S set
CYL851C