

Linear Vertical and O

Left: Red
Model shown 5L18R

Right: White
Model shown
LD1809W



33 - PREMIER RANGE

TUBULAR RADIATORS

Feel the heat. Linear stands tall and shimmers with reflected light. This radiator's elegant stature will enhance any modern kitchen or bathroom.

Choose any RAL colour to create a stunning focal point that also delivers on heat output.

Linear O is available in a Micrograin Matt Red Finish.



Linear Vertical

MS RAL 9016 B GY C 6 95 °C C V 5 YEARS
MATERIAL FINISH WORKING PRESSURE WORKING TEMP. CLOSED SYSTEM MOUNTING POS. WARRANTY

PRODUCT NAME	DIMENSIONS			PIPE CENTRES mm	WALL TO PIPE CENTRE mm	WALL TO FACE mm	WATER CONTENT lt	GROSS WEIGHT kg	FUEL OPTIONS E/H/D	PIPES OR SECTIONS	HEAT OUTPUT AT ΔT 50		RETAIL PRICE £
	Height mm	Length mm	Depth mm								BTU	Watts	
LS1505	1500	268	48	50-358	45	76	3.3	11.8	E/H/D	5	1486	435	
LS1507	1500	374	48	50-464	45	76	4.6	16.0	E/H/D	7	2080	609	
LS1509	1500	480	48	50-570	45	76	5.9	20.3	E/H/D	9	2674	783	
LS1805	1800	268	48	50-358	45	76	3.9	14.2	E/H/D	5	1810	530	
LS1807	1800	374	48	50-464	45	76	5.4	19.1	E/H/D	7	2534	742	
LS1809	1800	480	48	50-570	45	76	7.0	24.1	E/H/D	9	3258	954	
LS2005	2000	268	48	50-358	45	76	4.3	15.5	E/H/D	5	2015	590	
LS2007	2000	374	48	50-464	45	76	6.0	21.0	E/H/D	7	2821	826	
LS2009	2000	480	48	50-570	45	76	7.7	26.5	E/H/D	9	3627	1062	
LD1505	1500	268	61	50-358	66	97	6.6	20.8	E/H/D	10	2579	820	
LD1507	1500	374	61	50-464	66	97	9.2	29.1	E/H/D	14	3921	1148	
LD1805	1800	268	61	50-358	66	97	7.8	25.3	E/H/D	10	3381	990	
LD1807	1800	374	61	50-464	66	97	10.9	34.7	E/H/D	14	4734	1386	
LD1809	1800	480	61	50-570	66	97	14.0	44.2	E/H/D	18	6087	1782	
LD1811	1800	586	61	50-676	66	97	17.1	53.6	E/H/D	22	7439	2178	
LD2005	2000	268	61	50-358	66	97	8.6	27.9	E/H/D	10	3723	1090	
LD2009	2000	480	61	50-570	66	97	15.4	48.8	E/H/D	18	6701	1962	

Linear O

MS R 6 95 °C C V 5 YEARS
MATERIAL FINISH WORKING PRESSURE WORKING TEMP. CLOSED SYSTEM MOUNTING POS. WARRANTY

PRODUCT NAME	DIMENSIONS			PIPE CENTRES mm	WALL TO PIPE CENTRE mm	WALL TO FACE mm	WATER CONTENT lt	GROSS WEIGHT kg	FUEL OPTIONS E/H/D	PIPES OR SECTIONS	HEAT OUTPUT AT ΔT 50	
	Height mm	Length mm	Depth mm								BTU	Watts
Linear 5L18	1800	252	60	342-1750	45-55	85-95	3.1	10.5	H	5	2380	698

See Page 84 For Colours & Finishes

RECOMMENDED ACCESSORIES
See Page 87 For More Valves & Accessories



CYLINDER - Manual Angle Valve Pair Complete With 15mm Tube Connectors
CYL840C



Corner Thermostatic Valve & TRV Head
UAW853CT