

# Sovran Horizontal

## TUBULAR RADIATORS

Sheer confidence. An elegant radiator which uses convected heat to make this level of style affordable for every home. Sovran radiators feature a high output steel panel convector inside a 304 stainless steel brushed matt cover.



Above: Brushed Matt  
Model shown SOVD605H

SS MATERIAL    
 S FINISH    
 10bar WORKING PRESSURE    
 120°C WORKING TEMP.    
 OC OPEN/CLOSED SYSTEM    
 V MOUNTING POS.    
 5 YEARS WARRANTY

PRODUCT NAME	DIMENSIONS			PIPE CENTRES mm	WALL TO PIPE CENTRE mm	WALL TO FACE mm	WATER CONTENT lt	GROSS WEIGHT kg	FUEL OPTIONS E/H/D	HEAT OUTPUT AT AT 50	
	Height mm	Length mm	Depth mm							BTU	Watts
SOVD604h	605	405	72	50-495	55-75	90-110	2.4	16.3	H	24	2329 682
SOVD605h	605	505	72	50-595	55-75	90-110	3.0	20.1	H	30	2910 852
SOVD606h	605	605	72	50-695	55-75	90-110	3.6	23.9	H	36	3491 1022
SOVD607h	605	705	72	50-795	55-75	90-110	4.2	27.7	H	42	4075 1193
SOVD608h	605	805	72	50-895	55-75	90-110	4.7	31.4	H	48	4655 1363
SOVD609h	605	905	72	50-995	55-75	90-110	5.3	35.2	H	54	5239 1534
SOVD610h	605	1005	72	50-1095	55-75	90-110	5.9	39.0	H	60	5820 1704
SOVD611h	605	1105	72	50-1195	55-75	90-110	6.5	42.8	H	66	6401 1874
SOVD612h	605	1205	72	50-1295	55-75	90-110	7.1	46.5	H	72	6985 2045
SOVD614h	605	1405	72	50-1495	55-75	90-110	8.3	54.1	H	84	8150 2386
SOVD616h	605	1605	72	50-1695	55-75	90-110	9.5	61.6	H	96	9311 2727
SOVD618h	605	1805	72	50-1895	55-75	90-110	10.6	69.2	H	108	10476 3068
SOVD620h	605	2005	72	50-2095	55-75	90-110	11.8	76.7	H	120	11640 3409

See Page 84 For Colours & Finishes

RECOMMENDED ACCESSORIES  
See Page 87 For More Valves & Accessories



INTERAXIAL Swivel 50 Valve Pair  
Complete with 15 Tube Connectors &  
Domignon Sensor  
UDS927



DÉCOR Straight Valve Pair  
Complete with 15mm Tube  
Connectors  
UDS851